

ARC-HKIV05



8CH, TVI+ANALOG+IP. NETWORKABLE, USB, VGA, IPHONE, ANDROID VIEWABLE, DDNS 1.5U CASE

Description	ARC-HKIV05
Video/Audio input	
Video compression	H.264
Analog and HD-TVI video input	8-CH
	BNC interface
	(1.0Vp-p, 75?)
Supported camera types	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
Audio compression	G.711u
Audio Input	4-ch, RCA (2.0 Vp-p, 1 K?)
Two-way audio in	1-ch, RCA (2.0 Vp-p, 1 K?)
Video/Audio output	
HDMI / VGA output	1920 x 1080 / 60 Hz, 1280 x 1024 / 60 Hz, 1280 x 720 / 60 Hz, 1024 x 768 / 60 Hz
CVBS Output	1-ch, BNC (1.0Vp-p, 75?), Resolution: PAL 704x576, NTSC 704x480
Encoding resolution	Main stream: 1080P / 720P / 960H / 4CIF / CIF
	Sub-stream: 960H(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame rate	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate
Video bitrate	32 Kbps-10 Mbps
Audio output	2-ch, RCA (Linear, 1K?, for VGA output and CVBS output respectively)
Audio bitrate	64 Kbps
Dual-Stream Support	Support
Stream Type	Video, Video & Audio
Synchronous	8-CH

playback
Playback resolution 1080P / 720P / VGA / 960H / 4CIF / CIF / QVGA / QCIF

Network management

Remote connections 128
Network protocols TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS

Hard Disk

Type 4 SATA interfaces for 4 HDDs; 1 eSATA interface
Capacity Up to 4 TB capacity for each disk

External Interface

Network interface 1; 10M / 100M / 1000M self-adaptive Ethernet interface
Serial interface RS-232, RS-485, Keyboard
USB port 3 × USB2.0
Alarm in / out 16 / 4

General

Power supply 100 - 240VAC, 47 - 63HZ
Consumption ? 40W

(without hard disks)

Working temperature -10 °C ~+55 °C (14 °F ~ 131 °F)
Working humidity 10% ~ 90%
Chassis 19-inch rack-mounted 1.5U chassis
Dimensions (W × D × H) 445 × 390 × 70mm (17.5 × 15.3 × 2.7 inch)
Weight ? 5Kg (11.0lb)

(without hard disks)