

ARC-NVRH08



8 CH IP + 8 CH Analog Hybrid NVR STAND ALONE

Description

40Mbps Bit Rate Input Max(up to 8-ch Analog video + 16 IP video), 8 SATA interfaces, alarm I/O: 16/4, 2U case, 19"

ARC-NVRH08

Video/Audio

input

Video H.264

compr

ession

Analo 8-ch,

g BNC(1.0Vp-p,

video 75?),

input PAL / NTSC

self-adaptive

IP 16-ch

video

input

Comp Up to 16-ch

osite (Analog video +

video IP video)

input

Audio OggVorbis

compr

ession

Audio 8-ch,

input Audio 1-4: RCA

(2.0Vp-p, 1k?)

Audio 5-8:

DB26 connector

Two-w1-ch, BNC (2.0Vp-p, 1k?)

ay
audio
input
Video/Audio
output
HDMI 1-ch, resolution:
output 1920 × 1080P /60 Hz ,
1600 × 1200 /60 Hz,
1280 × 1024 /60 Hz,
1280 × 720 /60 Hz, 1024
× 768 /60 Hz
VGA 1-ch, resolution:
output 1920 × 1080P /60 Hz ,
1600 × 1200 /60 Hz, 1280
× 1024 /60 Hz, 1280 ×
720 /60 Hz, 1024 × 768
/60 Hz
Playback 5MP / 3MP / 1080P /
ack resolution UXGA / 720P / WD1 /
solution 4CIF / VGA / 2CIF / CIF /
n QCIF
CVBS 1-ch, BNC (1.0 Vp-p, 75
output ?), resolution: PAL: 704 ×
576, NTSC: 704 × 480
Video 4-ch
spot BNC (1.0 Vp-p, 75 ?),
output resolution: PAL: 704 ×
576, NTSC: 704 × 480
Video 8-ch,
loop BNC (1.0 Vp-p,
output 75 ?)
Encoding WD1 / 4CIF / 2CIF / CIF /
resolution QCIF
Frame rate 25 fps (P) / 30 fps /N
Video 32 Kbps-8192 Kbps, or
bit user defined (Max. 8192
rate Kbps)
Audio 2-ch, RCA (2.0 Vp-p, 1
output k?)
Audio 16 Kbps
bit
rate
Dual-stream Support, (Sub-stream at
stream CIF / QCIF: 25 fps (P) /
30 fps /N)
Stream type Video, Video & Audio
Synchronous 16-ch
ronous
s play
back
Hard disk
SATA 8 SATA interfaces for 4
HDDs + 1 DVD-R/W
(default), or 8HDDs
eSATA 1 eSATA interface
A
Capacity Up to 4TB capacity for
ity each disk
External
interface
Network 2, RJ45 10M / 100M /
rate up to 1000M self-adaptive
rface Ethernet
Serial 1 RS-232 interface (for
interface parameters configuration,
ce maintenance, transparent

channel); 1 RS-485
interface (for PTZ
control);
1 RS-485 keyboard
interface (for special
keyboard control)

USB i 2, USB2.0

nterfa
ce

Alarm 16

in

Alarm 4

out

General

Power 100 ~ 240 VAC, 6.3A, 50
supply ~ 60Hz

Consu ?70W (without hard disk
mptionor DVD-R/W)

Worki -10°C ~ +55°C (14°F ~
ng te 131°F)

mpera

ture

Worki 10% ~ 90%

ng hu

midity

Chass 19-inch rack-mounted 2U

is chassis

Dimen 445 x 470 x 90 mm

sions (17.52" x 18.5" x 3.54")

(W x

D x H)

Weigh ? 8kg (17.64 lb) (without
t hard disk or DVD-R/W)